KVASER
Advancing connectivity

Kvaser USBcan Pro 2xHS v2 CB

Learn more about this product









Your Gateway to Efficient Connectivity

The USBcan Pro 2xHS v2 CB is a bare circuit board version of Kvaser's USBcan Pro 2xHS v2 dual channel CAN or CAN FD interface with scripting capability, the USBcan Pro 2xHS v2 CB is supplied 'bare board' i.e. without a housing, and can thus be built into any system.

The Pro version is shipped with Kvaser TRX, a lightweight development environment that lowers the bar when starting out programming the device.

Warranty
2-Year warranty. See our general conditions and policies for details.

Support
Free support for all products by contacting support@kvaser.com

EAN
73-30130-00877-9

Ref. No. 98324-3 v. 2.1

KVASER
Advancing connectivity

Kvaser USBcan Pro 2xHS v2 CB

Major Features

- Plug-and-play installation.
- Supports both 11-bit (CAN 2.0A) and 29-bit (CAN 2.0B active) identifiers.
- Power derived from the USB-connection.
- High-speed CAN connection (compliant with ISO 11898-2), up to 1 Mbit/s.
- Kvaser MagiSync provides automatic time synchronization between several PC-to-bus interfaces connected to the same PC.
- Optimize protocol handling, pre-filter CAN messages directly on the interface, or simulate missing hardware with programming functionality.
- Compatible with J1939, CANopen, NMEA 2000® and DeviceNet. Higher layer protocol translation handled by the user's application. For software support please see our Technical Associates products and our Software Download page (www.kvaser.com).

Support

Documentation, Kvaser SDK and drivers can be downloaded for free at www.kvaser.com/downloads.

Kvaser SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, Visual Basic, Python and t script language.

Kvaser CAN hardware is built around the same common software API. Applications developed using one device type will run without modification on other device types.

Technical Data

CAN Bitrate	50-1000 kbps
Channels	2
Connectors	Molex 6-pin
CAN FD	Yes
Dimensions	42 x 100 x 6 mm
Error Frame Detection	Yes
Galvanic Isolation	Yes
Host interface	USB
Operative Systems	Linux, Windows [1]
Power Consumption	250 mA at 5 V
Regulatory Compliance	CE, FCC
Silent Mode	Yes
***t*-Script**	Yes
Temperature Range	-40 to +85 °C
Timestamp Resolution	1 µs
Weight	20 g

[1] Windows 7, 8, 10 (IA-32 and x86-64)
Windows 11 (x86-64)

Kvaser AB
Aminogatan 25A
SE-431 53 Mölndal
Sweden

Sales
sales@kvaser.com

Support
support@kvaser.com

Order
order@kvaser.com

kvaser.com

Ref. No. 98324-3 v. 2.1